

POLYTOP

E x p o r t e r f r o m c h i n a

PTDM30L BELT TYPE MILLING & DRILLING MACHINE**Specifications**

Max. drilling capacity	∅32mm (1 1/4 _{i±})
Max. diameter of face milling cutter	∅76mm (3 _{i±})
Max. diameter of end milling cutter	∅20mm (1 1/8 _{i±})
Swing	∅405mm (15 7/8 _{i±})
Max. distance from spindle nose to table	457mm (18 _{i±})
Spindle taper	MT-3 (R-8)
Max. spindle travel	130mm (5 _{i±})
Spindle barrel diameter	75mm (3 _{i±})
Range of spindle speed	100-2080 r.p.m/50Hz 120-2500 r.p.m/60Hz
Step of spindle speed	12 steps
Rotation angle of headstock	360 °
Column diameter	115mm (4 1/2 _{i±})
Longitudinal travel of table	200mm (7 7/8 _{i±})
Transverse travel of table	600mm (23 2/3 _{i±})
Table area	806mm _i ×240mm(31 3/4 _{i±} ×9 3/7 _{i±})
Motor power	1 1/2HP (1.1KW) / 2HP (1.5KW)
Motor voltage	110V/60HZ or 220V/50HZ
Total height	1100mm(43 1/3 _{i±})
Total length	1170mm(46 1/16 _{i±})
Total width	1010mm(39 3/4 _{i±})
Gross weight	360KGS(790LB)
Net weight	290KGS(640LB)
Packing size	980mm _i ×760mm _i ×1150mm

NOTE: SPECIAL COLUMN HEIGHT CAN BE INCREASED 150mm

ii