

POLYTOP

Exporter from china

PTDM40 GEAR TYPE MILLING & DRILLING MACHINE



Specifications

Max. drilling capacity	φ40mm (1 9/16 _{i±})
Max. diameter of face milling cutter	φ76mm (3 _{i±})
Max. diameter of end milling cutter	φ28mm (1 1/8 _{i±})
Swing	φ545mm (21 1/2 _{i±})
Max. distance from spindle nose to table	450mm (17 3/4 _{i±})
Spindle taper	MT-3 (R-8)
Max. spindle travel	120mm (4 3/4 _{i±})
Spindle barrel diameter	75mm (3 _{i±})
Range of spindle speed	95-1600 r.p.m/50Hz 120-1970 r.p.m/60Hz
Step of spindle speed	6 steps
Rotation angle of headstock	360 °
Rotation angle of spindle	±180 °
Column diameter	115mm (4 1/2 _{i±})
Longitudinal travel of table	175mm (6 7/8 _{i±})
Transverse travel of table	500mm (19 5/8 _{i±})
Table area	730mm _i ×210mm(28 3/4 _{i±} ×8 1/4 _{i±})
Motor power	1HP (0.75KW)
Motor voltage	110V/60HZ or 220V/50HZ
Total height	1100mm(43 1/3 _{i±})
Total length	1095mm(43 1/9 _{i±})
Total width	1010mm(39 3/4 _{i±})

Gross weight	340KGS(750LB)
Net weight	270KGS(600LB)
Packing size	870mm;Á760mm;Á1200mm
ii	ii

ii