

PTDM45A Drilling & Milling Machine



Features:

- Milling, drilling, tapping, boring, reaming
- Wide and big table
- Milling head up & down by power (option)
- Worktable power feed (option)
- Headstock tilts 180°
- Micro feed precision
- Heavy-duty tapered roller bearing spindle
- Positive spindle lock
- Adjustable gibs on table
- Geared drive, lower noise
- Accurate position, strong rigidity, strong cutting power

Specifications	PTDM45A
drilling capacity Ø	31.5 mm (MT 3) ; 45 mm (MT 4)
milling capacity	80 mm (face) ; 32 mm (end)
spindle mount	MT 3 / MT 4 / R 8
speeds	75 - 1600 rpm (50 Hz) ; 90 - 1970 rpm (60 Hz)
quill stroke	120 mm
head swivel	± 90°
table travel X-axis	565 mm
table travel Y-axis	230 mm
spindle nose-to-table distance	470 mm
table setup area	800 x 240 mm
motor, 220V ~ 575V	1.1 kW
Measurement	850 x 760 x 1150 mm
weight	300kg

STANDARD ACCESSORIES: 1.A set of tools 2.Pulling bar 3.Adaftor 4.Oil gun 5.Drilling chuck

OPTIONAL ACCESSORIES: 1.Stand 2.Coolant 3.Lamp