

POLYTOP

E x p o r t e r f r o m c h i n a

PTDM7032 MILLING & DRILLING MACHINE**Specifications**

Max. drilling capacity	∅32mm (1 1/4 _{j±})
Max. diameter of face milling cutter	∅76mm (3 _{j±})
Max. diameter of end milling cutter	∅22mm (1 1/8 _{j±})
Swing	∅405mm (15 7/8 _{j±})
Max. distance from spindle nose to table	475mm (18 7/10 _{j±})
Spindle taper	MT-3 (R-8)
Max. spindle travel	125mm (4 8/9 _{j±})
Spindle barrel diameter	75mm (3 _{j±})
Range of spindle speed	80-2300 r.p.m/50Hz 100-2800 r.p.m/60Hz
Step of spindle speed	10 steps
Rotation angle of headstock	360 °
Rotation angle of spindle	∠ 450 °
Column diameter	115mm (4 1/2 _{j±})
Longitudinal travel of table	175mm (6 7/8 _{j±})
Transverse travel of table	500mm (19 5/8 _{j±})
Table area	730mm∠210mm(28 3/4 _{j±} ∠ 8 1/4 _{j±})
Motor power	1 1/2HP (1.1KW) / 2HP (1.5KW)
Motor voltage	110V/60HZ or 220V/50HZ
Total height	1150mm(45 1/3 _{j±})
Total length	1080mm(42 1/2 _{j±})
Total width	800mm(31 1/2 _{j±})

Gross weight	320KGS(705LB)
Net weight	250KGS(550LB)
Packing size	870mm;Á760mm;Á1200mm
ii	ii

ii