

POLYTOP

Exporter from china

PTDM7032W MILLING & DRILLING MACHINE



- Variable speed AC motor & DC motor, please select one.
- At low speed, keep large movement of cutting force and cutting power.

MODEL		PTDM7045W	PTDM7040W	PTDM7032W
Drilling capacity		45 mm	40 mm	32 mm
Face milling capacity		80 mm	80 mm	63 mm
End milling capacity		32 mm	32 mm	20 mm
Max. distance from spindle nose to table		400mm(500mm)	400mm(500mm)	400mm(500mm)
Min. distance from spindle axis to column		285 mm	285 mm	285 mm
Spindle travel		130 mm	130 mm	130 mm
Spindle taper		M.T.4 or R8	M.T.4 or R8	M.T.3 or R8
Range of spindle speed(2 steps)	Converter	100-1500/500-3000r.p.m.	100-1500/500-3000r.p.m.	100-1500/500-3000r.p.m.
	DC motor	50-750/800-2200r.p.m.	50-750/800-2200r.p.m.	50-750/800-2200r.p.m.
Swivel angle of headstock		±360°	±360°	±360°
Size of table		800x240mm 700x240mm	800x240mm 700x240mm	800x240mm 700x240mm
Forward and backward travel of table		175 mm	175 mm	175 mm
Left and right travel of table		500mm;400mm	500mm;400mm	500mm;400mm
Motor Power	AC motor	1.5Kw	1.5Kw	1.5Kw
	DC motor	1.8Kw	1.5Kw	1.2Kw

Input voltage (Single phase)		110V or 220V	110V or 220V	110V or 220V
Overall height (Without stand) (selec one)		1060mm(1300mm)	1060mm(1300mm)	1060mm(1300mm)
Net weight		310kg	305kg	300kg
Gross weight		360kg	355kg	350kg
Packing size		880x770x1140mm / 880x770x1400mm 1030x832x1140mm / 1030x832x1140mm		
Loading amount (overall height)	1060 mm	36pcs/20'container		
	1300 mm	18pcs/20'container		
		ii	ii	ii

ii ii