

# POLYTOP

Exporter from china

## DRILLING MACHINE----- PTDT SERIES



PTDT-16Q



PTDT-19G



PTDT-19GF



PTDT-32GF

Specifications\Model	PTDT-16Q	PTDT-16E	PTDT-16J	PTDT-16JF	PTDT-16EF
Drilling capacity (mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$
Chuck size (mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$
Table travel (mm/INCH)	190/ $7\frac{1}{2}$	365/ $14\frac{5}{8}$	365/ $14\frac{3}{8}$	830/33	830/33
Table size (mm)	200×190	∅290	∅312	∅312	∅290
Spindle travel (mm/INCH)	55/ $2\frac{3}{16}$	80/ $3\frac{1}{8}$	85/ $3\frac{1}{4}$	85/ $3\frac{1}{4}$	80/ $3\frac{1}{8}$
Distance spindle axis to column (mm/INCH)	125/5	182/ $7\frac{3}{16}$	182/ $7\frac{3}{16}$	182/ $7\frac{3}{16}$	182/ $7\frac{3}{16}$
Spindle taper	MT2	MT2	MT2	MT2	MT2

Column diameter (mm/INCH)	60/2 $\frac{3}{8}$	72/2 $\frac{7}{8}$	72/2 $\frac{1}{8}$	72/2 $\frac{7}{8}$	72/2 $\frac{1}{8}$
Spindle speeds range(50Hz)R.P.M	300-3190	250-3200	250-3200	250-3200	240-2700
Spindle speeds	12	12	12	12	16
Motor (HP)	1/2	1/2	1/2	1/2	1/2
Overall height (mm/INCH)	860/33 $\frac{7}{8}$	965/38	992/39	1575/62	1545/60
N. W/G. W (Kg)	40/43	53/57	65/69	70/74	58/62
Packing case dimensions (mm)	680;Á440;Á255	785;Á460;Á280	785;Á460;Á280	785;Á460;Á280 1450;Á150;Á150	785;Á460;Á280 1450;Á150;Á150

Specifications\Model	PTDT-19G	PTDT-19GF	PTDT-25GF	PTDT-32GF
Drilling capacity (mm/INCH)	19/ $\frac{3}{4}$	19/ $\frac{3}{4}$	25/1	32/1 $\frac{1}{4}$
Chuck size (mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$
Table travel (mm/INCH)	406/16	830/33	500/20	500/20
Table size (mm)	!Ö350	!Ö350	360;Á360	470;Á420
Spindle travel (mm/INCH)	100/4	100/4	125/5	125/5
Distance spindle axis to column (mm/INCH)	199/8	199/8	225/9	300/12
Spindle taper	MT2	MT2	MT3	MT4
Column diameter (mm/INCH)	80/3 $\frac{1}{8}$	80/3 $\frac{1}{8}$	92/3 $\frac{5}{8}$	92/4
Spindle speeds range(50Hz)R.P.M	250-3200	250-3200	160/2060	160-2060
Spindle speeds	12	12	9	9
Motor (HP)	3/4	3/4	1	1
Overall height (mm/INCH)	1100/43	1625/64	1475/58	1730/68
N. W/G. W (Kg)	95/105	95/112	158/185	173/210
Packing case dimensions (mm)	1050;Á600;Á300	800;Á560;Á340 1450;Á150;Á150	1430;Á430;Á570	1430;Á430;Á570
ii	ii	ii	ii	ii