

POLYTOP

Exporter from china

FOR PTDX SERIES OF DRILLING MACHINE TECHNICAL DATA:**PTDX16JF/PTDX16GF****PTDX19GF****PTDX25GF****PTDX32JF/PTDX32G**

Specifications\Model	PTDX-16JF	PTDX-16GF	PTDX-19GF
Drilling capacity(mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	19/ $\frac{3}{4}$
Chuck size(mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$
Table travel(mm/INCH)	830/33	830/33	830/33
Table size(mm)	∅312	∅312	∅350
Spindle travel(mm/INCH)	85/ $3\frac{1}{4}$	85/ $3\frac{1}{4}$	100/4
Distance spindle axis to column(mm/INCH)	182/ $7\frac{3}{16}$	178/7	199/8
Spindle taper	MT2	MT2	MT2
Column diameter(mm/INCH)	72/ $2\frac{7}{8}$	80/ $3\frac{3}{8}$	80/ $3\frac{1}{8}$

Spindle speeds range(50Hz)R.P.M	250-3200	250-3200	250-3200
Spindle speeds	12	12	12
Motor(HP)	1/2	1/2	3/4
Overall height(mm/INCH)	1575/62	1575/62	1625/64
N.W/G.W(Kg)	70/74	72/78	95/102
Packing case dimensions(mm)	785;Á460;Á280 1450;Á150;Á150	785;Á460;Á280 1450;Á150;Á150	800;Á560;Á340 1450;Á150;Á150

ii

Specifications\Model	PTDX-25GF	PTDX-32JF	PTDX-32G
Drilling capacity(mm/INCH)	25/1	32/1 $\frac{1}{4}$	32/1 $\frac{1}{4}$
Chuck size(mm/INCH)	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$	16/ $\frac{5}{8}$
Table travel(mm/INCH)	500/20	500/20	500/20
Table size(mm)	360;Á360	360;Á360	440;Á440
Spindle travel(mm/INCH)	125/5	125/5	125/5
Distance spindle axis to column(mm/INCH)	225/9	225/9	300/12
Spindle taper	MT3	MT4	MT4
Column diameter(mm/INCH)	92/3 $\frac{5}{8}$	92/3 $\frac{5}{8}$	102/4
Spindle speeds range(50Hz)R.P.M	160/2060	160-2060	160-2060
Spindle speeds	9	9	9
Motor(HP)	1	1	1
Overall height(mm/INCH)	1475/58	1730/68	1778/70
N.W/G.W(Kg)	158/185	173/210	205/280
Packing case dimensions(mm)	1430;Á430;Á570	1430;Á430;Á570	1760;Á570;Á570
ii	ii	ii	ii