

# POLYTOP

Exporter from china

## PTXZ30 Vertical Drilling Machine



Model	PTXZ30	PTXZ30A	PTXZ30B
Max. Drilling Capacity (mm)	31.5	31.5	31.5
Max. Tapping Capacity (mm)	20	20	20
Max. travel of spindle (mm)	135	135	160
Distance from axis of spindle to generating line of column (mm)	315	315	315
Max. distance from spindle nose to surface of worktable (mm)	685	685	685
Max. distance from spindle nose to surface of base worktable (mm)	1195	1195	1195
Max. adjustment of worktable rest (mm)	580	580	580
Spindle taper bore	MT3/MT4	MT3/MT4	MT3/MT4
Spindle speed steps	12	12	12
Spindle speed range	80~2800	80~2800	75~2700
Spindle feed steps	ii	3	3
Spindle feed range	ii	0.12~0.32	0.12~0.32
Dimension of worktable (mm)	500 X 450	500 X 450	500 X 450
Effective working area of worktable (mm X mm)	400 X 350	400 X 350	400 X 350
Power of motor (kw)	0.85/1.1	0.85/1.1	1/1.5
Power of cooling pump (kw)	ii	0.085	0.085
Spindle feed method	Manual	Mechanical	Electromagnetism
Machine dimension	910X515X1800	910X515X1800	910X515X2144
Machine weight (Net weight/Gross weight) kg	368/416	380/428	390/438
Package dimensions (L X W X H)	950X640X2010	950X640X2010	950X640X2350
ii	ii	ii	ii

