

# POLYTOP

Exporter from china

## PTXZ32Q Vertical Drilling Machine



| Model   | PTXZ32Q   |
|---|-----------|
| Max. Drilling Capacity (mm)                                       | 32        |
| Max. Tapping Capacity (mm)  | 20        |
| Max. travel of spindle (mm)                                       | 140       |
| Distance from axis of spindle to generating line of column (mm)   | 280       |
| Max. distance from spindle nose to surface of worktable (mm)      | 760       |
| Max. distance from spindle nose to surface of base worktable (mm) | 1270      |
| Max. travel of spindle box (mm)                                   | 320       |
| Max. adjustment of worktable rest (mm)                            | 460       |
| Swivel angle of spindle box                                       | ±45°      |
| Swivel angle of worktable   | ±45°      |
| Spindle taper bore  | MT4       |
| Spindle speed steps   | 12        |
| Spindle speed range   | 80~2800   |
| Spindle feed steps  | 3         |
| Spindle feed range  | 0.12~0.32 |
| Dimension of worktable (mm)                                       | 460 X 400 |
| Effective working area of worktable (mm X mm)                     | 400 X 350 |
| Power of motor (kw)   | 0.85/1.1  |

|  |                     |
|--|---------------------|
| <b>Power of cooling pump (kw)</b>                  | <b>0.085</b>        |
| <b>Spindle feed method</b>                         | <b>Mechanical</b>   |
| <b>Machine dimension</b>                           | <b>870X550X1820</b> |
| <b>Machine weight (Net weight/Gross weight) kg</b> | <b>440/488</b>      |
| <b>Package dimensions (L X W X H)</b>              | <b>950X640X2010</b> |
| <b>ii</b>  | <b>ii</b>           |

ii ii

ii