

POLYTOP

E x p o r t e r f r o m c h i n a

PTXZ35BQ Vertical Drilling Machine

Model	PTXZ35Q	PTXZ35BQ
Max. Drilling Capacity (mm)	35	35
Max. Tapping Capacity (mm)	24	24
Max. travel of spindle (mm)	160	160
Distance from axis of spindle to generating line of column (mm)	350	350
Max. distance from spindle nose to surface of worktable (mm)	640	640
Max. distance from spindle nose to surface of base worktable (mm)	1230	1230
Max. adjustment of worktable rest (mm)	600	600
Spindle taper bore	MT4	MT4
Spindle speed steps	12	12
Spindle speed range	64~2280	60~2200
Spindle feed steps	3	3
Spindle feed range	0.12~0.32	0.12~0.32
Dimension of worktable (mm)	540X480	540X480
Effective working area of worktable (mm X mm)	400 X 450	400 X 450
Power of motor (kw)	1.5/2.2	1.5/2.2
Power of cooling pump (kw)	0.085	0.085
Spindle feed method	Electromagnetism	Electromagnetism
Machine dimension	1080X600X1950	1080X600X2305
Machine weight (Net weight/Gross weight) kg	560/615	570/625
Package dimensions (L X W X H)	1120X690X2130	1120X690X2130

ii

ii

ii

ii ii

ii