

POLYTOP

Exporter from china

PTWX639A TURRET MILLING MACHINE:



CHARACTER:

Double 55° swallowtail guide way is adopted on both Y-and Z-axis, so it is easy to adjust and easy to repair. Adopted strengthen rib on both sides of the column that makes the machine rigidly and beautiful.

MODEL	PTWX639A	PTWX639B	PTWX6310	PTWX6310A	PTWX6310B
Table size	230;Á1067 mm (9";Á42")		254;Á1270 mm (10";Á50")		
	230;Á1246 mm (9";Á49")		254;Á1370 mm (10";Á54")		
Long travel	650 mm	840 mm	850 mm		950 mm
Cross travel	305 mm		420 mm	400 mm	400 mm
Vertical travel	400 mm		420 mm		
T-slot No. and size	3;Á16				
Ram travel	312 mm		469 mm		
Distance from spindle nose to table surface	0-415 mm		0-445 mm		
Distance from spindle center to column	170-482 mm		140-609 mm		
Spindle hole taper	(Standard): R8 (Optional): ISO30 /ISO40				
Spindle travel	127 mm				
Spindle speed	(standard):(shift grade) 50HZ:65-4500 60HZ:80-5440 (optional): (variable) 65-4200				
Auto. quill feed	(three steps): 0.04(0.0015") / 0.08(0.003") / 0.15(0.006") mm/revolution				
Spindle motor	2.25 KW / 3PH				
Head swivel	90;ã	90;ã	90;ã	90;ã	90;ã
Head tilting	45;ã	45;ã	45;ã	45;ã	45;ã
Dimension of package	one miller per case	1400;Á1476;Á2030 mm		1516;Á1550;Á2080 mm	
	two miller per case	1450;Á1570;Á2080 mm		1650;Á1790;Á2170 mm	
	three miller per case	1450;Á2180;Á2080 mm		1650;Á2285;Á2235 mm	
Weight	1100 kg	1160 kg	1550 kg	1380 kg	1420 kg

MODEL	PTWX6310C	PTWX6310D	PTWX6311	PTWX6311A	PTWX6312	PTWX6312A
Table size	254;Á1270 mm (10";Á50")		305;Á1370 mm (12";Á54")		330;Á1370 mm (13";Á54')	
	254;Á1370 mm (10";Á54")		305;Á1500 mm (12";Á60")		330;Á1500 mm (13";Á60')	
Long travel	850 mm	950	920 mm	1000	840 mm	1000 mm
Cross travel	420 mm		380 mm		368 mm	
Vertical travel	420 mm		430 mm		530 mm	
T-slot No. and size	3;Á16					
Ram travel	469 mm		652 mm			
Distance from spindle nose to table surface	0-445 mm		0-450 mm		0-550 mm	
Distance from spindle center to column	140-609 mm		108-760 mm			
Spindle hole taper	(standard) ISO40					
Spindle travel	127 mm					
Spindle speed	(standard): (shift grade) 50HZ:65-4500 60HZ:80-5440					
	(optional): (variable) 65-3750					
Auto. quill feed	(three steps): 0.04(0.0015") / 0.08(0.003") / 0.15(0.006") mm/revolution					
Spindle motor	3.75 KW / 5HP					
Head swivel	90;ã	90;ã	90;ã	90;ã	90;ã	90;ã
Head tilting	FIX	45;ã	45;ã	FIX	45;ã	FIX
Dimension of package	one miller per case	1516;Á1550;Á2080 mm		1566;Á1650;Á2080 mm		1800;Á2016;Á2180 mm
	two miller per case	1650;Á1790;Á2170 mm		1720;Á1800;Á2175 mm		1800;Á2200;Á2180 mm
	three miller per case	1650;Á2285;Á2235 mm		ii		ii
Weight	1590 kg	1590 kg	1700 kg	1750 kg	2300 kg	2350 kg