

POLYTOP

Exporter from china

PTHQ400/A MULTI-PURPOSE MACHINE



MODEL		PTHQ400/A (PTHQ400/B;PTHQ400/L)
TURNING	Swing over bed	420mm
	Distance between centers	400mm
	Max. longitudinal travel	380mm (PTHQ400/3L:480mm)
	Max. cross travel	120mm
	Taper of spindle	M.T.3
	Spindle hole	∅20mm
	Step of speed / Range of speed	7 / 160-1360r.p.m.
	Barrel travel	70mm
	Taper of center	M.T.3
	Metric thread can be cut	0.2-3mm
	Inch thread can be cut	8-120T.P.I.
	Longitudinal range of automatic feeding	0.05-0.175mm (0.002-0.007∅)
	Cross range of automatic feeding	∅
DRILLING & MILLING	Drilling capacity	∅15mm
	Table size (L x W)	200x150mm ²
	End mill capacity	∅20mm
	Face mill capacity	∅63mm
	Spindle travel	∅85mm
	Spindle taper	M.T.3
	Steps of spindle speed / Range of spindle speed	14 / 117-1300r.p.m.
Swiveling angle of headstock	∅360°	
MOTOR	Main motor power / Drilling and milling motor	0.55Kw
	Voltage/Frequency	As customer's requirement

	Motor speed	1400r.p.m.
SHIPMENT DATA	Overall size	970 x 580 x 965mm (PTHQ400/3L:1070x580x890mm)
	Packing size	1032 x 580 x 1100mm (PTHQ400/3L:1130x580x1070mm)
	Net weight/Gross weight	180kg/215kg (PTHQ400/3L:185kg/226kg)
	Loading amount	40pcs/20'container
		ii