

POLYTOP

Exporter from china

PTK50/90 CNC LATHE



Machine data		PTK50	PTK90
Maximum Swing		410mm	410mm
Maximum Turned Diameter		170mm	230mm
Maximum Turned Length		350mm	450mm
Bed Inclination		60°slant	60°slant
Spindle Centre Height(from floor)		900mm	900mm
Spindle Nose		A ₂ -5	A ₂ -5
Hydraulic Power Chuck		170mm(4000rpm) 130mm(6000rpm)	170mm(4000rpm) 170mm(6000rpm)
Spindle Bore		54mm	61mm
Bar Capacity		42mm	52mm
Spindle Bearings (internal diameter)		80mm	90mm
Maximum Spindle Speed	Standard	4000rpm	4000rpm
	Option	6000rpm	6000rpm
Spindle Motor		5.5KW	11KW
X Axis Rapid Traverse Rate		10m/min	10m/min
Z Axis Rapid Traverse Rate		20m/min	20m/min
Turret:	Tooling type	VDI 30	VDI 30
	Number of tooling stations	12	12
Coolant Tank Capacity		100 litres	100 litres
CNC Controller		FANUC 21i	FANUC 21i
Approx. Floor Area		2.5m ²	2.8m ²

Approx. Machine Weight	2722kgs(6000 lbs)	2760kgs(6084 lbs)
ii	ii	ii