

**POLYTOP**

E x p o r t e r f r o m c h i n a

**PTKDVM930L/1130L VERTICAL MACHINING CENTERS**

<b>Machine data</b>	<b>PTKDVM930L</b>	<b>PTKDVM1130L</b>
Table size	930;Á510mm	1130;Á510mm
X travel	800mm	1100mm
Y travel	510mm	510mm
Z travel	510mm	510mm
Distance between spindle center and column guide way	550mm	550mm
Distance between spindle end and table	155-660mm	155-660mm
Taper bore of spindle	BT40	BT40
Spindle speed	8000rpm	8000rpm
X;Y;Z Travel speed	0-20m/min	0-20m/min
Table T slot number & width	3-18	3-18
Max. Table load	600Kg	600Kg
X;Y motor torque	12NM	12NM
Z motor torque	12NM	12NM
X;Y;Z motor connection	Direct connection	Direct connection
Tool number	24, 20	24, 20
Main motor power	7.5/11kw	7.5/11kw
Min. displacement (X/Y/Z)	0.001mm	0.001mm
Min. input (X/Y/Z)	0.001mm	0.001mm
Repeatability (X/Y/Z)	±0.003mm	±0.003mm
Overall dimensions (LxWxG)	2970x2100x2600mm	2970x2100x2600mm
Net weight	5000kg	5200kg
<b>Price USD</b>	<b>ii</b>	<b>ii</b>

ii