

POLYTOP

E x p o r t e r f r o m c h i n a

PTB11 6;Á2500 3-ROLLER BENDING MACHINE WITH ONE SIDE PREBEND

The up and down parts of PTW11 series three roller bending machine utilizes a machine construction. The transportation parts being machine driven. The upper roller can be moved up and down by the motor to discharge the workpiece. The machine can according to customer's requirement be supplied with specific rollers to work angle and steel pipe

Model	Maximum thickness (mm)	Maximum width (mm)	Yield limit (mpa)	Minimum diameter full capacity (mm)	Top roller diameter (mm)	Bottom roller diameter (mm)	Motor (kg)	Weight (kg)	Size (L. W. H.)
PTB11 Y16;Á2500	16	2500	245	600	320	250	7.5	11000	4660;Á1420;Á1640
PTB11 Y16;Á3100	16	3100	245	600	360	165290	11	13000	5260;Á1420;Á1640
PTB11 Y20;Á2500	20	2500	245	600	360	290	11	12000	4660;Á1420;Á1640
PTB11 10;Á1300	10	1300	245	400	210	190	5.5/2.2	2425	2940;Á1100;Á1270
PTB11 8;Á2500	8	2500	245	600	230	190	5.5/3	3485	4100;Á1100;Á1270
PTB11 8;Á2000	8	2000	245	400	210	190	5.5/3	2890	3700;Á1100;Á1270
PTB11 6;Á3100	6	3100	245	500	240	210	5.5/2.2	5390	4600;Á1150;Á1450

PTB11 6;Á2500	6	2500	245	400	210	190	5.5/3	3195	4100;Á1100;Á1270
ii	ii	ii	ii	ii	ii	ii	ii	ii	ii