

POLYTOP

Exporter from china

PTBD SERIES BENCH Lathe



Features:

- Guide-ways super-audio frequency quenched and precision ground to ensure long service life and high accuracy
- All headstock gears induction hardened and precision ground for smooth shifting and low noise
- Quick change D-8 cam lock spindle nose for fast chuck removal
- Large 1 1/2" thru spindle speed bore to enhance bar capacity
- 9 steps of main spindle speed ranging from 60 to 1200 rpm
- With removable gap block to increase swing in front of spindle
- With chuck guard, lead screw hood and tool-post protection board, conform to CE standards.
- Equipped with longitudinal stop
- Feed rod and lead screw interlocked
- Tailstock locked by eccentric wheel

ii

Specifications		PTB152;A500	PTB152;A750	PTB165;A1000
CAPACITIES	Max. swing over bed	304mm(12")	304mm(12")	330mm(13")
	Max. swing over cross slide	170mm(6 3/4")	170mm(6 3/4")	204mm(8")
	Max. swing over gap	430mm(17")	430mm(17")	464mm(18 1/4")
	Center distance	500mm(20")	750mm(30")	1000mm(40")
	Cross slide travel	186 (7 1/4")		
	Bed width	186 (7 1/3")		
SPINDLE	Spindle hole	1" (40mm) (1 1/2")		
	Spindle nose	ISO-D5		
	Spindle taper	Morse No.5		
	Spindle speeds	60-2000rpm (9Steps)		

FEEDS	Metric threads range (Kinds)	0.25-900 (20 Kinds)		
	Inch threads range (Kinds)	4-72 Inch (33 Kinds)		
	Module threads range (Kinds)	0.25-3.5 (12 Kinds)		
	Diametral threads range (Kinds)	8-144tio (30 Kinds)		
TAILSTOCK ii	Dia. of tailstock sleeve	!Ö40 (1 1/2;å)		
	Taper of tailstock sleeve	Morse No.3		
	Travel of tailstock sleeve	115		
MAIN MOTOR (kw)		1.1kw/1.5kw		
NET WEIGHT/GROSS WEIGHT (kgs)		480/580kgs	520/620kgs	650/750kgs
PACKING SIZE (L*B*H) 2SETS(cm)		140*115*167cm	165*115*167cm	190*115*167cm