

POLYTOP

Exporter from china

PTRZ32X7P RADIAL DRILLING MACHINE



Standard accessories:

- Drill chuck $\varnothing 16\text{mm}$
- Taper sleeve
- Arbor
- Drift
- Box shape worktable

Special accessories:

- Stand
- Angle vice
- Safety guard

Characters :

- With wide range of speed , with manual & power feeds. The feed of machines are very easily engaged and disengaged at any time.
- The radial arm can rotated and can tilted $\pm 45^\circ$, it reliable and easy job can be done.
- Main parts are made by machine center which import form KIA with high precision and efficiency, ensuring reliability and high quality.
- The machine with small appearance and much function, the machine widely used for drilling, counterboring, tapping, etc.

Model	PTRZ32;Á7P
Max. Drilling capacity (mm)	32
Max. Tapping capacity (mm)	Cost Iron20 Steel16
Distance spindle axis to column generating line	300;«700
Diameter of column (mm)	150
Spindle taper	MT3
Spindle travel	150
Spindle speeds range (mm)	100;«1600
Spindle speeds series	8
Spindle feeds (mm/r)	0.08;ç0.14;ç0.23
Rotary angle of rocker in hirizontal plane(jã)	360
Distance between spindle nose to working surface of base (mm)	275;«680
Dimension of Base (mm)	250;Á250;Á250
Diameter of base (mm)	1200;Á625;Á155
Overall size (mm)	1235;Á625;Á1230
Motor (w)	750 or 1100
G. W./ N.W. (Kg)	675/580
Packing dimension (cm)	123;Á69;Á138
ii	ii