

POLYTOP

Exporter from china

DENSE PERMANENT MAGNETIC CHUCKS:



Dense permanent magnetic chuck can be used for location processing magnetic conduction workpieces. in surface grinder. tool grinder and electric sparks machine tools. magnetic even. high precision.

Model	British standard	Dimensions			pole pitch (mm)	Magnetic (N/cm ²)	Weight (kg)	Overall Dimensions of container (cm)
		L	W	H				
XM41 125;Á250	5;Á10"	250	125	50	1+3	;Ý80	13	35;Á23;Á12
XM41 150;Á150	6;Á6"	150	150	50	1+3	;Ý80	9.5	24;Á24;Á12
XM41 150;Á300	6;Á12"	300	150	50	1+3	;Ý80	19	40;Á25;Á12
XM41 150;Á350	6;Á14"	350	150	50	1+3	;Ý80	22	44;Á25;Á12
XM41 150;Á400	6;Á16"	400	150	50	1+3	;Ý80	25	50;Á25;Á12
XM41 150;Á450	6;Á18"	450	150	50	1+3	;Ý80	28	57;Á25;Á12
XM41 200;Á400	8;Á16"	400	200	55	1+3	;Ý80	34	53;Á30;Á12
XM41 200;Á450	8;Á18"	450	200	55	1+3	;Ý80	38	57;Á30;Á12
XM41 200;Á500	8;Á20"	500	200	55	1+3	;Ý80	42	64;Á30;Á12